

VKH13

Technical Data – bidder details



TOILET CUBICLE SYSTEM

MODEL:

TYPE VKH13 of SCHÄFER

Trennwandsysteme GmbH, D-56593
Horhausen, Phone (+49) 2687/91510,
UK Partners: C&B Systems, 25 Church
Road Teddington, TW11 8PF
Phone (+44) 208 977 2968

The system is certificated by the German
Association for Technical Inspection and
has the GS symbol. Systems without this
symbol are not genuine.

To prove the sustainability of the product, the
system must be PEFC™ or FSC™ certified.
The corresponding certificate must be
presented. Systems without valid PEFC™ or
FSC™ certification are not genuine.

CONSTRUCTION:

Waterproof solid grade laminate panels in
conjunction with colour-coated, vertical and
horizontal aluminium profiles.

WALLS AND DOORS:

Solid grade laminate panels, 13 mm thick,
and designed to be moisture resistant,
rot-proof, scratch and impact resistant.

DESIGN:

Vertical full height aluminium round profiles,
40 mm diameter, with integrated door
striker strips and rubber strips for silent
operation on both sides of the door. Pad
tape as silencer is not permitted.

Running over the front wall is a horizontal,
continuous aluminium profile, 68.5 x 160
mm, secured to the brickwork with special
brackets.

The vertical profiles have to be drilled into
the horizontal headrail to guarantee a very
high stability. The headrail encompasses the
vertical profiles with a min. of 30mm.

Butt-joints underneath the headrails are not
permitted.

Screw joints with only one screw are not
permitted either.

Horizontal and vertical profiles are grooved
for the 13mm HPL panel. Connection of
profiles and panels are made with high
performance glue. Visible screw joints are
not permitted.

Wall connections are made with aluminium
U-profiles. Profiles are rounded in the back
to cover any drilling holes completely.

HARDWARE:

Self-closing doors through three
maintenance-free hinges from stainless
steel or aluminium with high-performance
polymers. Spring hinges are not permitted.
Hinges are screwed-on to the vertical round
profile with stainless steel screws.
Fastening of the hinges with rivets are not
permitted.

Hinges on the door's side are connected
with stainless steel shoulder bolts.

Self-tapping screws are not permitted.

Dead lock with a plastic cover. Plastic door
knob. On the inside with a rosette and an
olive and on the outside with a
vacant/engaged indicator and with an
emergency unlocking device.

FEET:

From a span of 4.5 m and at the outer
corners of the cubicle supporting feet from
aluminium tube (recommended for panel
widths from 500 mm), diameter 40 mm,
screwed-on to the floor with welded-on tube
for insertion of vertical, full height aluminium
round profiles.

STANDARD ACCESSORIES:

One coat hook per cubicle, one door buffer.

COLOURS:

Panels and hardware according to
manufacturer's colour-chart.

All profiles powder coated according to
manufacturer's colour-chart.

HEIGHT:

Standard height approx. 2120 mm
incl. 155 mm clearance.

C&B Systems Water Solutions Centre,
25 Church Road, Teddington, TW11 8PF
Email: sales@c-bgroup.co.uk
Website: www.c-bgroup.co.uk
Tel: (+44) 208 977 2968